

Precision Engineered Recessed Luminaires

Illumicare's Demeter luminaire is designed with an 88mm (3 1/2") low-profile flange and recessed body for flush mounting into concrete, stone, wood or other flush surfaces, providing illumination of steps and low level features. The louvered cover reduces light spillage, providing an excellent glare-free illumination.

This luminaire has a precision engineered, beveled 316 stainlesssteel flange which sits securely in a PVC sleeve. The luminaire may be removed from the PVC sleeve and mounted directly as well.

This luminaire has a 3mm (1/8") thick tempered recessed glass lens, covered by a stainless steel grate, which stops water pooling and depositing dirt on the bulb.



DEMETER

Construction:	316 Marine Grade Stainless Steel
Dimensions:	2.95" x 3.46"
Lamp:	LED MR16*
Wattage:	Maximum 10 Watts
Lens:	1/8" Flat Tempered Glass
Socket:	Ceramic MR16 Socket
Wire:	36" UL Listed Lead Wire
Weight:	2.35 lbs
Includes:	PVC Installation Sleeve
Voltage:	12V

*Lamp not included



Recommended LED Lamps

LED 6W VWW 15 SP	6W MR16 2700K 15° Spot
LED 6W VWW 45 FL	6W MR16 2700K 45° Flood
LED 6W WW 15 SP	6W MR16 3000K 15° Spot
LED 6W WW 30 NFL	6W MR16 3000K 30° Narrow Flood
LED 6W WW 45 FL	6W MR16 3000K 45° Flood
LED 6W NW 15 SP	6W MR16 4000K 15° Spot
LED 6W NW 45 FL	6W MR16 4000K 45° Flood
LED 6W CW 15 SP	6W MR16 5500K 15° Spot
LED 6W CW 45 FL	6W MR16 5500K 45° Flood
LED 2X WW 15 SP	2X MR16 3000K 15° Spot
LED 2X WW 30 NFL	2X MR16 3000K 30° Narrow Flood
LED 2X WW 45 FL	2X MR16 3000K 45° Flood

Mounting

Suitable for insertion into turf and garden beds or recessed in wood and masonry. For best results, mount level with the surface.

