

Precision Engineered Recessed Luminaires

Orion is designed to be installed either horizontally or vertically, in lawns, stone, wood, masonry and other architecture. When recessed, Orion sits almost flush with the surface and can be stepped on, or run over by equipment and light vehicles, without causing damage to the luminaire.

This luminaire has precision engineered 316 stainless steel flange which sits securely in a PVC sleeve with two screws. The luminaire may be removed from the PVC sleeve and mounted directly as well.

This luminaire has a 3mm (1/8") thick tempered recessed glass lens which stops water pooling and depositing dirt on the bulb.



ORION

Construction:	316 Marine Grade Stainless Steel
Dimensions:	2.95" x 3.46"
Lamp:	LED MR16*
Wattage:	Maximum 10 Watts
Lens:	1/8" Flat Tempered Glass
Socket:	Ceramic MR16 Socket
Wire:	36" UL Listed Lead Wire
Weight:	2.35 lbs
Includes:	PVC Installation Sleeve
Voltage:	12V

*Lamp not included



Recommended LED Lamps

LED 6W VWW 15 SP	6W MR16 2700K 15° Spot
LED 6W VWW 45 FL	6W MR16 2700K 45° Flood
LED 6W WW 15 SP	6W MR16 3000K 15° Spot
LED 6W WW 30 NFL	6W MR16 3000K 30° Narrow Flood
LED 6W WW 45 FL	6W MR16 3000K 45° Flood
LED 6W NW 15 SP	6W MR16 4000K 15° Spot
LED 6W NW 45 FL	6W MR16 4000K 45° Flood
LED 6W CW 15 SP	6W MR16 5500K 15° Spot
LED 6W CW 45 FL	6W MR16 5500K 45° Flood
LED 2X WW 15 SP	2X MR16 3000K 15° Spot
LED 2X WW 30 NFL	2X MR16 3000K 30° Narrow Flood
LED 2X WW 45 FL	2X MR16 3000K 45° Flood

Mounting

Suitable for insertion into turf and garden beds or recessed in wood and masonry. For best results, mount level with the surface.

